

MATERIAL DATA SAFETY SHEET

DECKING AND RAILING

VERSION 00



Section 1- PRODUCT AND COMPANY INFORMATION:

Product Names: The Rockies Decking Range

Brand Name: Timmdek Pty (Ltd).

Address: 5 Station Road, Unit 2, 7441, Montague Gardens, Cape Town.

Telephone: +27 (21) 300 0112

Section 2- COMPONENT AND INGREDIENT INFORMATION:

Component	Units	Data	Standard	Result
Pb content	mg/Kg	<1000mg/Kg	EPA 3050B: 1996	NA
Cd content	mg/Kg	<1000mg/Kg	BS EN1122: 2001	NA
Hg content	mg/Kg	<1000mg/Kg	EPA 3052: 1996&EPA 7473:1998	NA
Chromium (VJ)	mg/Kg	<1000mg/Kg	EPA 3060A: 1996&EPA 7196A	NA
polybrominated biphenyl	mg/Kg	<1000mg/Kg	EPA 3540C&EPA 3550C	NA
Polybrominated Diphenyl	mg/Kg	<1000mg/Kg	EPA 3540C&EPA 3550C	NA

Section 3- HAZARDS IDENTIFICATION:

Emergency Overview

Contact with strong oxidizers or exposure to temperatures greater than 400F may cause a fire. Smoke may contain carbon monoxide aldehydes and other toxic materials. Airborne wood and plastic dust may explode when combined with an ignition source.

Potential Health Effects

EYE: Dust may irritate eyes.

SKIN: Dust may cause skin irritation.

INGESTION: Not known.

INHALATION: Dust can cause irritation to mucous membranes and the upper respiratory tract. Wood dust is considered a carcinogen.

Section 4- FIRE FIGHTING MEASURES:

FLAMMABLE PROPERTIES:

Flash point: Not applicable.

Combustible: Material may burn on contact with oxidizers or ignition sources.

FLAMMABLE LIMITS:

Lower flammable limit: Not applicable.

Upper flammable limit: Not applicable.

AUTOIGNITION TEMPERATURE: Typically 400-500°.

EXPLOSION HAZARD: Airborne concentrations of combustible dust, when combined with an ignition source, can cause an explosion hazard if the dust concentration exceeds 30-60g/m³.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, carbon monoxide, nitrogen oxides, aldehydes, cyanides, and other hazardous gases, vapors, and particles.

EXTINGUISHING MEDIA: Water, dry chemical and other agents rated for a wood fire (Type A fire). Use an extinguisher rated for a Type A fire.

FIRE FIGHTING INSTRUCTIONS: Evacuate the area and notify the fire department. If possible isolate the fire by moving other combustible materials. If the fire is small, use a hose-line or extinguisher rated for a Type A fire. If possible, dike and collect water used to fight fires. Fire fighters should wear normal protective equipment (full bunker gear) and positive-pressure self-contained breathing apparatus.

Section 5-ACCIDENTAL RELEASE MEASURES:

Not Applicable.

Section 6-HANDLING AND STORAGE HANDLING:

Provide ventilation or other measures so that dust levels are below the exposure limits listed in Section 2.

STORAGE: Keep dust away from ignition sources and store in a closed container. Consult NFPA 68 and 70 for additional information.

Section 7-EXPOSURE CONTROLS/PERSONAL PROTECTION:

ENGINEERING CONTROLS: Keep the airborne dust concentrations below the exposure limits. Maintain adequate ventilation in the work area.

RESPIRATORY PROTECTION: When respiratory protection is required, or dust concentrations are unknown, use a NIOSH/M SHA approved air-purifying respirator.

SKIN PROTECTION: Wear work gloves to prevent skin irritation.

EYE PROTECTION: Wear ANSI-approved eye protection.

Section 8-PHYSICAL AND CHEMICAL PROPERTIES:

BOILING POINT: NA	DENSITY: 28-70 lb/ft ³
MELTING POINT: NA	PH: NA
VAPOR PRESSURE: NA	ODOR: None
VAPOR DENSITY: NA	APPEARANCE: Shiny solid, various colors
SOLUBILITY IN WATER: NA	

Section 9-STABILITY AND REACTIVITY:

CHEMICAL STABILITY: (CONDITIONS TO AVOID) Stable.

INCOMPATIBILITY: Keep away from high temperatures and strong oxidizers, such as concentrated nitric acid, oxygen, hydrogen peroxide, and chlorine.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, hydrogen cyanide, and other products of wood combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

Section 10-TOXICOLOGICAL INFORMATION FOR WOOD DUST AND TITANIUM DIOXIDE:

WOOD DUST (softwood) and TITANIUM DIOXIDE

Wood dust and titanium dioxide have been classified NIOSH-Ca or "potential occupational carcinogen, with no further categorization".

Teratology (Birth Defect) Information: No hazards reported.

Reproduction Information: NO hazards reported.

Reproduction Information : No hazards reported.

Sensitizer : NO hazards reported.

Section 11-ECOLOGICAL INFORMATION:

These wood products are not expected to pose an ecological hazard as a result of their intended uses.

FLAMMABLE LIMITS:

Lower flammable limit: Not applicable.

Upper flammable limit: Not applicable.

Section 12-DISPOSAL CONSIDERATIONS:

Dispose of waste according to local, state/provincial, and federal requirements.

Section 6-HANDLING AND STORAGE HANDLING:

Provide ventilation or other measures so that dust levels are below the exposure limits listed in Section 2.

STORAGE: Keep dust away from ignition sources and store in a closed container. Consult NFPA 68 and 70 for additional information.

Section 13-TRANSPORTATION INFORMATION-Hazardous Materials Table 172.101:

Shipping Name	N	Packing Group	N
Hazard Class	N	Placards/Labels	N
Identification No.	N	Special Provisions	N

Section 14-REGULATORY INFORMATION:

OSHA: Hazard Communication	CFR 1910.1200 (b)(6)(iv)	CERCLA RQ:	NA
EPCRA EHS RQ Section 302:	NA	EPA CAA SECTION 112	NA
EPCRA Section 313:	NA	Uniform Fire Code	NA

Section 15-OTHER INFORMATION:

This MSDS is intended solely for safety education and not for use as specifications or warranties. The information in the MSDS was obtained from usually reliable sources and is provided without any representation for warranties regarding the accuracy or correctness. Since the handling, use, and storage is beyond our control, LP assumes no responsibility and disclaims liability for any loss, damage, or expense arising therefrom.