



# PR56

*Load-bearing rail for decking.*

## PR56

REF	DESCRIPTION	QTY/PALETTE	COMPATIBILITY
1197	<b>PR56 - 124</b> 32 clips for 16 boards of 120 mm. 56 x 55 x <b>1984</b> mm.	108 pcs	Accoya®, Kebony®, Moso®, Thermofrêne, Thermpin
1197	<b>PR56 - 124</b> 64 clips for 32 boards of 120 mm. 56 x 55 x <b>3968</b> mm.	108 pcs	
2035	<b>PR56 - 145</b> 26 clips for 13 boards of 140 mm. 56 x 55 x <b>1885</b> mm.	108 pcs	UPM
1196	<b>PR56 - 150</b> 26 clips for 13 boards of 145 mm. 56 x 55 x <b>1950</b> mm.	108 pcs	Nekko
1972	<b>PR56 - 155,5</b> 24 clips for 12 boards of 150 mm. 56 x 55 x <b>1866</b> mm.	108 pcs	Dex
1644	<b>PR56 WITHOUT CLIPS</b> For tapered boards. 56 x 55 x <b>1984</b> mm.	108 pcs	

## TECHNICAL CHARACTERISTICS

<b>Rail material</b>	Aluminum 6060
<b>Rail finish</b>	Black paint
<b>Clip material</b>	Polyoxymethylene (POM)
<b>Rail weight (including clips)</b>	+/- 1,70 kg/ml
<b>Maximum length</b>	3968 mm
<b>Pull-out strength of the clip on the rail</b>	150 to 250 kg, for two fixing points (depending on the type of board)

- Load-bearing rail, pedastal spacing up to 120 cm for private use.
- Industrially pre-clipped rail for perfect drainage lines
- Each board can be removed individually with special keys adapted to the width of the board
- Rail can be cut to length
- No contact between the boards and the aluminum rail for better air circulation
- Invisible fastening
- Simple, quick and comfortable installation
- Infinite possibilities
- 100% recyclable