



# FLAT RAIL

*Rail for wall and ceiling cladding*

REF	DESCRIPTION	QTY/PALETTE	CONSUMMATION INDICATIVE PER M <sup>2</sup>
1185	<b>FLAT RAIL - clip spacing 124 mm</b> 32 clips for 16 boards of 120 mm 12 x 55 x <b>1984</b> mm.	216 pcs	0,85 pc
1187	<b>FLAT RAIL - clip spacing 71 mm</b> 28 clips for 28 boards 12 x 55 x <b>1988</b> mm.	216 pcs	0,85 pc
1792	<b>FLAT RAIL - clip spacing 70 mm</b> 28 clips for 28 boards 12 x 55 x <b>1960</b> mm.	216 pcs	0,85 pc
1799	<b>FLAT RAIL - clip spacing 51 mm</b> 39 clips for 39 boards 12 x 55 x <b>1989</b> mm.	216 pcs	0,85 pc
2480	<b>FLAT RAIL - VARIBO</b> 32 clips for 25 boards 12 x 55 x <b>1968</b> mm.	216 pcs	0,85 pc
2191	<b>FLAT RAIL - clip spacing 46 mm</b> 43 clips for 43 boards 12 x 55 x <b>1978</b> mm.	216 pcs	0,85 pc

## TECHNICAL CHARACTERISTICS

<b>Rail material</b>	Aluminum 6060
<b>Rail finish</b>	Black paint
<b>Clip material</b>	Polyoxymethylene (POM)
<b>Rail weight (including clips)</b>	+/- 0,630 kg/ml
<b>Maximum length</b>	3968 mm
<b>Pull-out strength of the clip on the rail</b>	150 to 250 kg, for two fixing points (depending on the type of board)

- **Non load-bearing rail** to be used for wall or ceiling cladding
- Thin
- Industrially pre-clipped rail for perfect drainage lines
- Each board can be removed individually with special keys adapted to the width of the board
- Rail can be cut to length
- No contact between the boards and the aluminum rail for better air circulation
- Invisible fastening
- Simple, quick and comfortable installation
- Infinite possibilities
- 100% recyclable